

Patent Claims

1. A high-voltage outdoor bushing arrangement (1) having an electrically insulating casing (6) and switch-disconnector module which has an electrically conductive housing (2), with a phase conductor which can be interrupted into a first section (7) and a second section (8) by means of an isolating gap (11) extending along an axis (3) through the bushing arrangement (1), in which case a switching piece or an element of a multiple part switching piece can be moved at an angle to the axis (3).

2. The high-voltage outdoor bushing arrangement (1) as claimed in claim 1, characterized in that at least one of the sections (7, 8) can be grounded by means of a grounding switch, which is arranged within the electrically conductive housing (2), by continuation of a further movement of the switching piece.

3. The high-voltage outdoor bushing arrangement (1) as claimed in one of claims 1 or 2, characterized in that the movable switching piece is driven via a shaft (15) which passes through the essentially cylindrical housing.

4. The high-voltage outdoor bushing arrangement (1) as claimed in one of claims 1 to 3, characterized in that the contact piece is in the form of a blade contact.

1 5. The high-voltage outdoor bushing arrangement (1) as
2 claimed in one of claims 1 to 3, characterized in that the
3 contact piece is in the form of a pin.

4
5 6. The high-voltage outdoor bushing arrangement (1) as
6 claimed in one of claims 1 to 5, characterized in that the
7 isolating gap (11) is held in the housing (2) via pillar
8 supports.

9
10 7. The high-voltage outdoor bushing arrangement (1) as
11 claimed in one of claims 1 to 6, characterized in that the
12 contact piece can be moved on a curved path.

13
14 8. The high-voltage outdoor bushing arrangement (1) as
15 claimed in one of claims 3 to 7, characterized in that the
16 shaft (15) passes through an outer wall of the housing (2) in a
17 cylindrical area of the housing (2).